



PRECISION THERMAL RIFLE SCOPE

TI-GEAR-S325

The TI-GEAR-S325 is the professional-grade thermal weapon sight for aiming and engagement on a wide variety of firearms at short- to and medium-range distances. Ideal for both small, large-size caliber rifles, machine guns, whether single or repetitive shooting. It is also a great tool for reconnaissance and tactical surveillance.

The latest generation silent and Auto-NUC sensor is at the base of the TI-GEAR-S325. GSCI proprietary hardware and software solutions are built around the sensor and offer exceptional image quality along with unique tools for added tactical advantage and user safety.

The TI-GEAR-S325 is fully dust- and waterproof, meets and exceeds modern standards. The TI-GEAR-S325 is designed for both professional users and also firearms enthusiasts. It is a robust, reliable tool for long-term, intensive use in any environment, in any lighting or weather conditions.

ADVANTAGES OF TI-GEAR-S325

Comfortable Eyepiece
with Long Eyerelief

Full-Size Colour
AMOLED Display

Canadian-Made,
ITAR-Free System

All-Aluminum Rugged Housing

Multi-Use Picatinny Side
Mounting Bracket

High-Performance, Auto-NUC, Shutterless, Silent FPA

Smooth and Precise Focus Adjustment

Fast Germanium
Objective Lens

Variety of Rifle Mounts Available



9001:2015





Designed, Developed, Manufactured by GSCI Advanced Photonics
120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA
WWW.GSCI.NET | GSCI@GSCI.NET | +1.905.850.0990

DISCLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Startington, and the product represents measurable weight of all components the product represents measurable size of the body including all optical components attached and in fully folded position. Dimensions of additions such as optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, objective learning and/or battery extensions may vary and therefore are not instructed.





PRECISION THERMAL RIFLE SCOPE

TI-GEAR-S325

Every TI-GEAR-S325 Sight can be used in 3 main configurations



Hand-Held

Removing Weapon Mount is not necessary



Standalone Sight



Clip-On (In-Line) Sight

Clip-On Adapter Required, Scope Adapter Optional (Configuration-Dependent)





ADVANCED PHOTONICS

PRECISION THERMAL RIFLE SCOPE TI-GEAR-S325

	Optical Magnification	1.5X
	Objective Lens System	25mm
	Field of View	14.9°x11.2°
	Focusing Range	0.5m Infinity
	Diopter Adjustment Range	-6 +4
	Eyerelief	Min. 50mm
	FPA Type	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation)
	FPA Resolution and Pitch	384x288, 17µm
	FPA Sensitivity (NETD)	<40mK
	FPA Refresh Rate	50Hz
	Digital Zoom	1X, 2X, 4X
	Internal Display	Full Size: 0.6-Inch Diagonal, AMOLED, Colour, 800x600
크	Imaging Modes	Monochrome (White-Hot / Black-Hot) and Multiple Colour Palettes
-G	Shot-Initiated FOV Feature (SIF)	Built-In Adjustable Shock Sensor
П	Digital Passive Stadiametric Rangefinder (SRF)	Yes
\triangleright	Digital Detail Enhancement Feature (DDE)	Yes
7	Wide Dynamic Range Feature (WDR)	Yes
R-S3	Stow Safety Feature (SSF)	Yes
25	Integrated 9-Axis Absolute Orientation HUD (Heads-Up Display)	Optional: 3-Axis Sensors - Magnetometer, Accelerometer and Gyroscope
	Integrated Compass	Optional
一一	Pitch / Roll / Azimuth Indications	Optional
CHN	Real-Time Date-Time Stamp	Yes: Simplified, Extended, DTG Formats
Ż	Digital Video Recorder with Real-Time Stamp	Optional: Comes with removable 32GB microSD card
$\overline{\mathbb{C}}$	Electronic Reticles	8+8 Patterns, Easy Zeroing / Calibration
\triangleright	Detection Capability: Man (1.7x0.5m) / NATO Target (2.3x2.3m)	830m / 1130m
	Hand-Held Capability	Yes: Tripod-Mountable + Helmet-Mountable (Weapon mount has to be removed)
DAT	Conversion to Clip-On (In-Line) Sight	Yes
\overline{A}	User Profiles (Configurable)	Yes: 8
\triangleright	Automatic/Manual Pixel Masking	Yes
	Reset to Factory Defaults	Yes
	External Video Feed Protection	Yes
	Automatic Power Down Control	User-Configurable: 10 60 minutes of inactivity
	Accepted Batteries	2 (two) CR123 of Any Type: Lithium / Rechargeable
	Universal Port	Video-Out, Remote Control and External Power (4VDC 15VDC)
	Battery Life on 2x CR123	Up to 7 Hours
	Environmental Protection	Fully Waterproof
	Dimensions	140 x 60 x 60 mm
	Weight	365 grams
	Operating Temperature	-40°C +50°C
	Warranty	7 Years, Limited
	Made In Canada	ITAR-Free





ADVANCED PHOTONICS PRECISION THERMAL RIFLE SCOPE

TI-GEAR-S325

STANDARD EQUIPMENT: WHAT'S IN THE BOX		
1	Thermal Imaging Sight	
2	Long Eyerelief Rubber Eyecup (Attached)	
3	Front Lens Protective Cover (Attached)	
4	Adjustable Dual Quick Release Weapon Mount DQRM (PICATINNY, with fine-tune knobs for tolerance adjustments)	
5	Demist Shield	
6	USB Power Cable	
7	Video-Out Cable	
8	Soft Carrying Pouch	
9	User Manual	
10	Quick Reference Card	
11	Waterproof Hard Carrying Case	
12	Cleaning Kit (3-in-1 Multi-Pen + Cleaning Cloth)	

^{*} Batteries not included

	OPTIONAL EQUIPMENT
Α	Advanced Helmet Mount GR8 ™
В	J-Arm Adapter Interface J-Arm-TI
С	Helmet Mounting Harness HMH-1
D	Universal Remote Control Unit TRC-120 (Comes with connection cable)
Е	Universal Multi-Voltage Battery Pack MVP-240™ (Comes with connection cable)
F	Built-In Digital Video Recorder GS-DVR-INT (Comes with 32GB microSD card and SD adapter)
G	External Digital Video Recorder GS-EDVR (Comes with set of cables and 32GB SD card)
Н	MTAR™-HUD Heads Up Display (streams video directly from the unit; equipped with built-in DVR, GPS and Integrated 9-Axis Absolute Orientation HUD)
ı	Portable Head-Mounted Display HMD-800-MOD (streams thermal video directly from the device, comes with connection cable)
J	Integrated 9-Axis Absolute Orientation HUD (Heads-Up Display), 3-Axis Sensors for Compass Reading, Inclinometer/Pitch Reading, and Level/Roll Reading
K	Dual Lever Adjustable Rifle Mount DLM (<i>PICATINNY</i> , with fine-tune knobs for tolerance adjustments)
L	Heavy-Duty Quick Release Rifle Mount MAK-QR-BLASER (Blaser, Adapter included)
М	Heavy-Duty Quick Release Rifle Mount MAK-QR-PICATINNY (PICATINNY, Adapter included)
N	Heavy-Duty Rifle Mount MAK-PICATINNY (PICATINNY, Adapter included, Allen Key Included)
0	Adapter for MAK Mount: Regular Length (ADAPTER-REG) or Extended Length (ADAPTER-EXT)
Р	Clip-On Adapter COA
Q	Day Scope Adapter Clamp for COA for direct mounting onto daytime optics, CO-DSA (various sizes available)

DISCLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Starlight act, inc. Mass, of the product represents measurable which to fall components this sole discretion of General Starlight act, mechanics, and optical starts of the product represents measurable size of the body including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, blackling to the product represents measurable size of the body including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, blackling to the product represents measurable size of the body including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, blackling to the product represents measurable size of the produ